



# Drum Closures

## Product Options Information Sheet

Francis Ward drum closures are a proprietary design featuring a buttress thread with a 50mm ID.

It is recommended that closures are regularly inspected to ensure all components are present and functioning correctly. Closures should be replaced after 2 years in service.



### Warboy / Warlord Standard Closure

Natural LMDPE with XLPE Foam seal. Embossed date of issue to regulate service life. Available in a range of colours



### Warboy / Warlord PRV Closure

Black LMDPE with XLPE Foam seal, vented with gas permeable, fluid impermeable membrane. Embossed date of issue to regulate service life.



### Warlord Standard Hand Tight Closure

Blue LMDPE with butyl rubber seal. Embossed date of issue to regulate service life. Closure seals at 7Nm of torque application.



### Warlord PRV Hand Tight Closure

Black LMDPE with butyl rubber seal, vented with gas permeable, fluid impermeable membrane. Embossed date of issue to regulate service life. Closure seals at 7Nm of torque application.



### Warlord Viton Hand Tight Closure

White LMDPE with green viton rubber seal. Embossed date of issue to regulate service life. Closure seals at 7Nm of torque application.

Whilst every attempt has been made to ensure that the information provided in this product information sheet is accurate and reliable Francis Ward cannot accept responsibility for the interpretation of the information provided. It is the responsibility of the user to determine the chemical compatibility of the container with its intended contents.



**Francis Ward** – A Division of The Rotational Mouldings Group

Brook House, 221 Bowling Back Lane, Bradford, BD4 8SJ, UK

Tel: +44 (0)1274 707030 | Fax: +44 (0)1274 724704 | Email: [sales@francisward.com](mailto:sales@francisward.com) | Web: [www.francisward.com](http://www.francisward.com)