



IBC Top Fittings

Product Options Information Sheet



50mm (2") Dual Action Vent (PP¹)

Provides both pressure relief for gaseous products and anti-vacuum when discharging IBC bottles.



50mm (2") CPP Vent (GRPP²)

Provides both pressure relief for gaseous products and anti-vacuum when discharging IBC bottles. Vents at 4+ psi.



50mm (2") Pressure Relief Vent (GRPP²)

Provides pressure relief for gaseous products.



50mm (2") Anti-vacuum Vent (GRPP²)

Provides anti-vacuum when discharging IBC bottles.



25mm (1") Fort Vale Vent (SS³)

Provides accurate pressure relief venting capability at 0.62 BAR (9 psi).



Male Cam Lock (SS³)

Accepts a variety of hoses and fittings. Supplied with a dustcap and seal. Available in a variety of sizes.



Male Cam Lock (GRPP²)

Accepts a variety of hoses and fittings. Supplied with a dustcap and seal. Available in a variety of sizes.



Drum valve system

A closed liquid transfer system. The dry break coupler enables quick and safe transfer of hazardous products.

¹ Polypropylene

² Glass Reinforced Polypropylene

³ Stainless Steel

Whilst every attempt has been made to ensure that the information provided in this product information sheet is accurate and reliable Francis Ward cannot accept responsibility for the interpretation of the information provided. It is the responsibility of the user to determine the chemical compatibility of the container with its intended contents.



Francis Ward – A Division of The Rotational Mouldings Group

Brook House, 221 Bowling Back Lane, Bradford, BD4 8SJ, UK

Tel: +44 (0)1274 707030 | Fax: +44 (0)1274 724704 | Email: sales@francisward.com | Web: www.francisward.com