



Vehicle
Certification
Agency



Maritime &
Coastguard
Agency



Department
for Transport



VCA Dangerous Goods Office
Cleeve Road, Leatherhead
Surrey, KT22 7NF, UK
T +44 (0)1372 226110
F +44 (0)1372 226116
E dgenquiries@vca.gov.uk
www.dft.gov.uk/vca

CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number: 6041

NOT TRANSFERABLE

Application No.: 8993

Issue number and date: 05 24/01/2018

Issued to: **HAYWOOD ROTO MOULDING t/a FRANCIS WARD**
Brook House
221 Bowling Back Lane
Bradford
West yorkshire
BD4 8SJ

Packaging type: 3H1

Description:

Jerrican, plastics, non-removable head

Capacity: 30 litres

Height: 474 mm

Body mass: 3 Kg

Tare: 3.045 kg

Section dimensions: 305 length x 288 width

Test Contents: Tested with ethylene glycol and water for liquids

Handle: Three handles moulded integrally into the top

CLOSURES: No in Head: 1 No in Body: 0

Plastics Size: 65mm Type: Plain or vented plastics screwcap Maker: Francis Ward Overcap: <input type="checkbox"/> Washer/wad and Closure Torque: PE Foam 30 Nm Nm	Plastics Size: 65mm Type: Plain or vented plastics screwcap Maker: Francis Ward Overcap: <input type="checkbox"/> Washer/wad and Closure Torque: Viton washer 7 Nm Nm	Plastics Size: 65mm Type: Plain or vented plastics screwcap Maker: Francis Ward Overcap: <input type="checkbox"/> Washer/wad and Closure Torque: Butyl 7 Nm Nm
--	--	---

Special Notes:

Product ref. 6400202

Additional options and chemical compatibility in schedule issue no n/a dated n/a.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:

DROP HEIGHT (m)

1.9

The packaging is approved, as provided in the relevant transport rule, to contain liquids of:

packing group

density (d)

gross mass (kg)

LEAKPROOFNESS (kPa)

20

I

-

-

STACKED AT 3m with RD (d)

1.9

II

1.9

61

INTERNAL PRESSURE (kPa)

100

III

1.9

61

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

U 3H1/Y1.9/100/**/GB/6041

Revalidation due by: 31/12/ 2023

For further details see www.vca.gov.uk

Signed:

Keith F.B. White

Keith F B White, Principal Consultant VCA DGO

** To be replaced by the last two digits of the year of manufacture